

Fujitsu recommends Windows Vista® Business.

LifeBook U1010

- World's smallest* tablet-convertible ultra-mobile PC
- Genuine Windows Vista® Home Premium
- All Ways, Always connectivity via 3.5G, built-in Wireless LAN, LAN and Bluetooth®
- Intelligently designed to suit your working style. Interact with U1010 like a Laptop, Tablet or Hand-held
- Versatile with convertible form factor and pen input capability

*As of May 2007, according to Fujitsu's Investigations.



	Specifications
Platform	Intel® Ultra Mobile platform 2007 - Intel® processor A110 (800MHz, 512KB L2 cache, 400MHz FSB) - Intel® 945GU Express Chipset - Intel® ICH7U I/O Controller Hub
Operating System	Genuine Windows Vista® Home Premium (or Genuine Windows Vista® Business) (or Genuine Windows® XP Tablet PC Edition)
Display	5.6-inch SuperFine WSVGA, 1024 X 600 pixels, Passive Touch Panel
Memory	1GB DDR2 400MHz
Hard Disk	40GB
Bluetooth®	v2.0
Battery	Up to 3hrs* (2-cell Li-Ion 2600mAh)
Weight	0.63kg
Detailed Specifications	
Hard Disk Drive	1.8-inch PATA Ultra DMA 100 (4200rpm), S.M.A.R.T. support, Two Partitions - 50/50 ⁶
Graphics	Integrated Intel® Graphics with 3D Accelerator
High Definition (HD) Audio	RealTek ALC262 HD audio codec with built-in digital microphone
Communication	Bluetooth® v2.0, RealTek 8101L 100Base Ethernet, Super AG™ wireless connection with dual antenna and Integrated Camera 0.3 Mega Pixel
User Interface	Keyboard with Glide Point: 56-key, 14mm key pitch, 1.3mm key stroke Fingerprint Sensor with vertical scroll functions
Card Slot	1 x Type I/II CF Card slot 1 x Secure Digital (SD) Card Reader
Connector Interface	USB 2.0 x 1, VGA (external display) and RJ45 (LAN) via LAN/ VGA adapter connector, Audio-in, Audio-out, Power Adapter DC-in 3.5G ⁸ Embedded 3.5G (HSDPA) WWAN connectivity with dual antenna. Up to 3.6Mbps ⁹ downlink. - Supports tri-band UMTS (HSDPA): 850, 1900, and 2100MHz - Supports quadband EDGE/GPRS/GSM: 850/900/1800/1900MHz
Quick Launch Panel	Two programmable application buttons, two programmable up/down key buttons, one rotation button, one Ctrl+Alt+Del button and one FnKey button
Security ⁴	User and supervisor BIOS password, Boot Sector Write Prevention, Fingerprint Sensor, Trusted Platform Module (TPM)
Dimensions	185mm (W) x 133mm (D) x 26.5-32.0mm (H)
Bundled Accessories	
AC Adapter	Input AC100~240V, Output DC16V 40W

Bundled Software	Microsoft Origami Experience Pack, Acronis True Image, Softex OmniPass, Adobe Acrobat Reader, Sun Microsystems Java Runtime, Fujitsu UpdateNavi ² , Fujitsu Hardware Diagnostic, Fujitsu Display Manager, 3G Watcher, Camera Capture Application, Microsoft Office Professional 2007 60-day Convertible Trial ³
Software on CD	1 year Full Licensed Norman Virus Control
VGA/LAN Adapter ²	External cable for connection to RJ45 (LAN), VGA (external display)
Carrying Case ²	Portable slip case
Optional Accessories	
Port Replicator	Connector Interface: USB 2.0 x 4, VGA (external display), RJ45 (LAN), Power Adapter DC-in
Extended Battery	4-cell Li-Ion 5200mAh 7.2V

The above information shows the general technical specifications of the product and does not represent actual configuration that would be sold in your region. For specific configurations and their availability, please check with your local distributors.

- Results obtained from BAPCo® MobileMark® 2002 performed on systems with maximum battery life settings under laboratory testing environment. Actual battery life will vary based on screen brightness, sound volume settings, running applications, connected peripherals, power management settings, battery conditioning, and other customer preferences in the real life situation. Built-in bay device or hard drive usage may also have a significant impact on battery life.
- Please check actual bundling with country local distributor.
- Super AG™ and Super G™ are trademarks of Atheros® Communications. Super AG™ and Super G™ modes deliver up to 108 Mbps raw data rate with typical end user throughput exceeding 60Mbps in a wireless network environment where wirelessly connected equipment are using Atheros Super AG™ or Super G™ enabled chipsets.
- BIOS Lock needs a supervisor/user password to access BIOS setup. BIOS settings can be configured to prompt for password at every first bootup or all bootup sequences. Access to BIOS setup is needed to configure Hard Disk Lock. Hard Disk Lock requires an access key to retrieve data on the hard disk. This is a Data Confidentiality security feature. LifeBook Lock requires a supervisor/ user password to bootup the LifeBook when it powers up or resumes last session from suspend/hibernate mode. This is an anti-theft feature with more than 800,000 password combinations using the buttons on the Quick Launch Panel. Anti-theft Lock Slot allows the use of a lock to physically secure the LifeBook. Smartcard slot usage is dependent on customer's solution. Fingerprint sensor uses AuthenTec TruePrint™ Technology and Softex OmniPass to remember customer list of user IDs and passwords. Full security unlock sequence - LifeBook Lock, Bootup Lock (BIOS Lock), Hard Disk Lock, Fingerprint Windows Logon.
NOTE: Loss of password requires the LifeBook to be returned to Japan factory for system refresh. Cost of shipment and lost data will be borne by the customer. Backup your user's profile before changing HDD. Without the user's profile associated with a document at the point of encryption, Softex OmniPass cannot decrypt the encrypted document.
- UpdateNavi is a Fujitsu Proprietary application that updates LifeBook drivers by connecting automatically to Fujitsu's server. This will help update your LifeBook with the latest software drivers and utilities to ensure compatibility between hardware and software, maintaining smooth operation anytime, anywhere.
- This refers to Windows Vista® hard disk drives C:\ and D:\. 50/50 refers to approximate 50% allocation of user accessible hard disk storage to C:\ and D:\ drives. For Windows Vista® hard disk drives, 1GB will be reserved for internal recovery usage which is not shown.
- Subjected to network and SIM capabilities. Data rates refer to download or upload speed which is also dependent on network capabilities and conditions.
- 3.5G module comes with a 1 year local carry-in warranty
- Microsoft Office Professional 2007 60-day Convertible Trial needs online activation to begin. 60-day starts from day of activation.

BAPCo® MobileMark® 2002 is the premier notebook battery life and performance under battery life metric based on real world applications for Windows® XP platforms.

It is natural for all thin-film transistor (TFT) liquid crystal displays (LCD) to show a small number of missing or discoloured dots. These are commonly known as non-conforming pixels. This is a technology limitation of TFT LCD and does not represent a defect. Fujitsu warranty does not cover limitations in technology such as non-conforming pixels.

Specifications reflected above are engineering and hardware specifications. They do not represent actual usage or operating dimensions, sizes, performances and weights as these are dependent on factors such as operating temperature, type of operating system and application used, connected devices and accessories as well as hardware configurations of the notebook. Please check the compatibility of 3rd party accessories before purchase. Ambient temperature: 5° to 35°C / 41 to 95°F (operating), -15° to 60°C / 5 to 140°F (non-operating). Relative humidity: 20% to 85% RH (operating), 8% to 85% RH (non-operating). Please note that, 1GB is equivalent to 1,073,741,824 bytes.

hk.fujitsu.com/pc

HONG KONG (Head Office):
Fujitsu PC
Asia Pacific Ltd
Tel : (852) 3101 8133
Fax : (852) 3101 0633
hk.fujitsu.com/pc

AUSTRALIA & NEW ZEALAND:
Fujitsu PC Australia
Toll Free: (AU) 1800 288 283
(NZ) 0800 288 283
Fax : (61-2) 9889 3360

CHINA:
Fujitsu PC China Division
Tel : (86-21) 3310 0808
Fax : (86-21) 3310 0606
cn.fujitsu.com/pc

INDIA:
Fujitsu India Limited
Tel : (91-11) 2370 6070
Fax : (91-11) 2370 6079

INDONESIA:
Fujitsu Indonesia
Tel : (62-21) 570 9330
Fax : (62-21) 573 5150

MALAYSIA:
Fujitsu PC Asia
Pacific Pte Ltd
Tel : (60-3) 7728 4868
Fax : (60-3) 7728 4830
my.fujitsu.com/pc

PHILIPPINES:
Fujitsu Philippines Inc.
Tel : (63-2) 812 4001
Fax : (63-2) 817 7576
ph.fujitsu.com/pc

SINGAPORE:
Fujitsu PC Asia
Pacific Pte Ltd
Tel : (65) 6776 0688
Fax : (65) 6776 0788
sg.fujitsu.com/pc

THAILAND:
Fujitsu Systems
Business (Thailand) Ltd
PC Division
Tel : (66-2) 263 7888
Fax : (66-2) 263 7880

TAIWAN:
Fujitsu Taiwan Ltd
Tel : (886-2) 2311 2255
Fax : (886-2) 2311 2277

VIETNAM:
Fujitsu Vietnam Ltd
Tel : (84-4) 831 3895
Fax : (84-4) 831 3898

Note: For countries not listed above, please contact our Hong Kong office.

All rights to the mentioned trademarks reside with their respective owners. Fujitsu endeavours to ensure that the information in this documentation is correct and fairly stated, but does not accept liability for any errors or omissions. The development of Fujitsu products and services is continuous and published information may not be up to date. It is important to check the current position with Fujitsu. The document is not part of the contract or licence save in so far as may be expressly agreed.

JOB NO.: 1862 • Printed by Fujitsu PC Asia Pacific Limited in November 2007. Information is correct at time of printing.